



## TRL Series

Experience unmatched stability, durability, and ease of use with the UK-made TRL Trade Roof Ladders, designed to make working at height on roofs safer and more efficient for trade professionals. The market-leading TRL is purpose-built to tackle the unique challenges of working on sloped surfaces and is used by industry-leading utilities providers, satellite installers, and Hire companies.

### Key Benefits

- **Secure Roof Placement:** Equipped with a heavy-duty ridge hook for exceptional stability on any roof surface.
- **Roof Protection:** Rubber bearer bars evenly distribute weight, preventing roof damage while you work.
- **Enhanced Safety:** Industrial non-slip circular rungs provide secure footing during use on pitched roofs.
- **Ease of Use:** Wall-running wheels added to the heavy-duty ridge hook for easy positioning.
- **Lightweight and Durable:** Aluminium roof ladder with box section stiles is lightweight without compromising strength.
- **Green Manufacturing:** Non-slip rungs produced with UK-sourced Recycled Low-Carbon Aluminium 4.0.
- **Multiple Size Options:** Available in single and double sections with a locking safety catch for additional security.



Available in 8 sizes



## Specifications

| Code   | No. of Sections | No. of Rungs | Weight kg | Closed Length mm | Extended Length mm | Largest Ladder Section Width mm | Smallest Ladder Section Width mm | Width of Ridge Hook mm |
|--------|-----------------|--------------|-----------|------------------|--------------------|---------------------------------|----------------------------------|------------------------|
| TRL130 | Single          | 11           | 9.0       | 2950             | 2950               | N/A                             | 325                              | 380                    |
| TRL140 | Single          | 15           | 12.0      | 3950             | 3950               | N/A                             | 325                              | 380                    |
| TRL150 | Single          | 19           | 14.0      | 4970             | 4970               | N/A                             | 325                              | 380                    |
| TRL155 | Single          | 21           | 15.0      | 5460             | 5460               | N/A                             | 325                              | 380                    |
| TRL230 | Double          | 20           | 14.5      | 3000             | 4670               | 400                             | 325                              | 380                    |
| TRL235 | Double          | 24           | 16.5      | 3450             | 5670               | 400                             | 325                              | 380                    |
| TRL240 | Double          | 28           | 18.5      | 3950             | 6670               | 400                             | 325                              | 380                    |
| TRL245 | Double          | 32           | 20.5      | 4450             | 7670               | 400                             | 325                              | 380                    |

